



Adjustable Trolleys TRTA



These ESD protected trolleys provide a flexible solution to product movement within the production area, extra shelves can be added as required. Height of all shelves can be adjusted by allen-key. Frames are of semiconductive epoxy powder coated steel in grey (RAL 7045). Shelves are of 12 mm ESD-laminate with semiconductive steel edging. Four conductive swivel castors Ø 125 mm of which 2 are braked.

Accessories

- End mesh panels NET 2 ESD
- Document holder DSA4 ESD

Part No.	Shelf Size D x W (mm)	Outer Dimensions D x W x H (mm)	No. of shelves	Load Capacity	Height adjustment of shelf	Extra Shelf
TRTA 4082 ESD	430 x 800	535 x 900 x 1015	2	150 kg	200...770 mm	TRHA 408 ESD
TRTA 4102 ESD	430 x 1000	535 x 1100 x 1015	2	150 kg	200...770 mm	TRHA 410 ESD
TRTA 5082 ESD	530 x 800	635 x 900 x 1015	2	150 kg	200...770 mm	TRHA 508 ESD
TRTA 5102 ESD	530 x 1000	635 x 1100 x 1015	2	150 kg	200...770 mm	TRHA 510 ESD
TRTA 4104 ESD	430 x 1000	535 x 1100 x 1535	4	300 kg	215...1340 mm	TRHA 410 ESD
TRTA 5104 ESD	530 x 1000	635 x 1100 x 1535	4	300 kg	215...1340 mm	TRHA 510 ESD
			Max Capacity per shelf 50 kg			

Reel Holder Trolley RRT



This modern, adjustable trolley is designed for the safe transport and storage of SMD reels. One trolley combination offers storage for up to 360 SMD spools.

1. Reel holder trolley RRT ESD

The basic unit consists of 3 supports for reel racks and a lower shelf. The perforated lower rail prevents dust build-up. The reel supports and lower shelf can be adjusted by allen-key. Frames, reel supports and lower shelf are of semiconductive epoxy powder coated steel in grey. 4 conductive swivel castors Ø125mm with brakes are provided. Load capacities: 50 kg/support and 200 kg/trolley.

Overall dimensions D x L x H : 540 x 1100 x 1785 mm.

Reel holders are ordered separately.

2. Reel rack RR ESD

Designed for use with SMD spools of 7", 13" and 15" size. The rack includes 15 fixed double compartments of 60 mm width. Frame is of semiconductive epoxy powder coated steel wire in grey (RAL7035). Full length, antistatic label holder. Load capacity 50kg. Racks are designed for standard metric shelving. Dimensions D x L x H: 426 x 960 x 254 mm

3. Document holder DSA4 ESD

Document stand A4. Semiconductive epoxy powder coated steel. Includes two magnets.